

TECHNICAL DATA SHEET | AUTOMOTIVE

Engen Xtreme S9 10W-40

High-Performance Semi-Synthetic Crankcase Engine Oil

Description

This motor oil is formulated using high-quality solvent-refined mineral and synthetic base oils. A carefully balanced selection of advanced additives provides the following performance characteristics.

Benefits & Features

- High and stable viscosity index
- A fast cold start
- A strong oxidation resistance
- Good detergency and dispersion
- A safe lubrication film at high temperatures
- A strong anti-wear, corrosion and foaming

Application

This lubricant is suitable for petrol, LPG, and diesel engines, including turbocharged and naturally aspirated engines, in passenger cars and vans.

Performance Level

Meets or exceeds the following performance levels:

- API: SN/CF
- ACEA: A3/B4
- MB: 229.1
- Renault: RN0700
- VW: 501.01/505.00

Typical Physical Characteristics

ENGEN XTREME S9 10W-40			
PARAMETERS	METHODS	UNITS	TYPICAL RESULTS
SAE No.	-	-	10W-40
Density at 15°C	ASTM D4052	Kg/l	0.860
Viscosity @ 40°C	ASTM D445	cSt	90.4
Viscosity @ 100°C	ASTM D445	cSt	13.7
Viscosity Index	ASTM D2270	-	154
Flash Point COC	ASTM D92	°C	224
Pour Point	ASTM D5950	°C	-39
Total Base No.	ASTM D2896	mgKOH/g	10.4
Sulphated ash content	ASTM D874	%	1.31

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to Engen's specification, variations in these characteristics may occur.

Handling and Precautions

When handling this product, maximum temperature of 60°C should be observed for storage, unloading and blending. However, it is strongly recommended that for long-term storage, temperature should not exceed 50°C.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water. For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS. Safety Data Sheets are available for all our products and should only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either Engen or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

+27 8600 36436

WEBSITE
https://www.engenlubricants.com/products/

EMAIL TECHNICAL SUPPORT
csctechnical@vivoenergy.com

VIVO ENERGY EGYPT, Nile City Towers, Northern Tower,
22nd floor, office No. 25 & 26, 2005 Corniche El Nil,
Ramlet Boulaq, Boulaq, Cairo

REVISON DATE: 27/10/2026
VE Egypt Technical Data Sheet